

HL-i Series

Digital Compact Scales

Compact & Portable

Resolution
up to
1 : 2,000

Clear LCD
Display



Multiple Weigh Modes:

- HL-200i: g, oz, ct & tael
- HL-2000i: g, oz, lb-oz & tael

Nin★JA
New Innovative Novel Japanese Apparatus

Easy Field Calibration

1,000 Hour Battery Life (Batteries Included)

Features

- Simple & Easy to Operate
- Rugged & Reliable Design with High-Impact Plastic Housing
- Accurate Reading over Wide Temperature Range
- 2 Year Warranty
- Portable (4 Type AA Batteries included)
- Clear LCD Display (0.53")
- Low Battery Indicator
- Weight Stability Indicator
- Auto Power Off (5 minutes)
- Separate Keys for Power & Re-Zero
- Portable (4 Type AA Batteries included)
- Optional AC Adapter

Model	Capacity	Resolution	Units of Measure	Pan Size
HL-200i	200g	0.1 g	g, oz, ct, tl	5.1" diameter
HL-2000i	2000 g	1 g	g, oz, lb-oz, tl	5.1" diameter

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278
Document #1015

www.andweighing.com

last saved:3/8/05

AND
A&D WEIGHING
...Clearly a Better Value



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119

Specifications

	HL-200i	HL-2000i
Gram (g)	200 g x 0.1 g	2000 g x 1 g
ounce (oz)	7.05 oz x 0.01 oz	70.5 oz x 0.1 oz
pound/Ounce (lb/oz)	-	4 lb 6.6 oz x 0.1 oz
Carat (ct)	1000.0 ct x 0.5 ct	-
Taiwan Tael (tl)	5.335 tl x 0.005 tl	53.35 tl x 0.05 tl
Non-Linearity	± 0.2 g	± 2 g
Repeatability	0.1 g	1 g
Span Drift	± 0.015% / °C typical (5°C ~ 35°C / 41°F ~ 95°F)	
Display	7 segment LCD, 0.53 inch / 13.5 mm height	
Display Update	5 times per second	
Pan Size	5.1" diameter / 130 mm	
Dimensions	130 (W) x 192 (D) x 51 (H) mm 5.1 (W) x 7.6 (D) x 2.0 inches	
Battery Life (Approx.)	1,000 continuous hours with alkaline type cells @ 20°C / 68°F 5 minute sleep mode	
Operating Temp.	-10°C ~ 40°C / 14°F ~ 104°F RH less than 85%	
Weight (Appx.)	500 g / 1.1 lb	
Power	4 AA size batteries (included) or AC Adapter (Option)	
Calibration Weight (optional)	200g	2000g

Specifications are subject to change without notice

Options:

- FV-05 Adapter AC (110V)
- FV-06 Adapter AC (220V)

Accessories:

- AD-1700-200G ..Weight Mass 200g
- AD-1700-2KGWeight Mass 2000g

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #1015

www.andweighing.com

last saved:3/8/05



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119